



ITeam LendiT™ Library Material Dispensing System

LendiT™ is the latest product from ITeam, which dispenses items to library patrons anywhere in your area. This could be in your local community center, train or bus station, office buildings, shopping centers or malls and countless other locations, the possibilities are endless.

LendiT™ can hold 200, 500, or 1000 items depending on your needs and size of items. LendiT™ is ergonomic and environmentally friendly. Designed and manufactured with a low carbon footprint, the unit is also styled to meet ergonomic and ADA guidelines. Its modular design allows for easy add on options such as credit cards, coin and bill acceptors. Special attention was given to make this unit easy and accessible for staff to maintain and manage.

Features:

- Material capacity is from 200 to 1000 items
- Issue and return materials
- Reservations and customer pick up
- First screen is branded and customized with key operational instructions
- Search options by category e.g. author, title, blue ray, DVD etc.
- Borrowers barcode card reader included for user account access
- Flip screen technology for fast search of materials
- System uses RFID tag identifier in conjunction with live ILS connection
- Items displayed with correlating image and details for easy selection



iTeam Resources Inc, USA. P.O. Box 547651; Orlando, FL 32854

Tel. (678) 261-4002 x235 ~ www.iteaminc.com

Specifications subject to change without notice. ©2013



iTeam LendiT™ Library Material Dispensing System

Specifications:

Physical size of hardware:

| | LendiT™ 200 | LendiT™ 500 | LendiT™ 1000 |
|--------|-------------|-------------|--------------|
| Height | 78" | 78" | 78" |
| Width | 44" | 79" | 192" |
| Depth | 44" | 44" | 44" |
| Weight | 480 lbs. | 1720 lbs. | 4498 lbs. |

Materials:

Powder coated steel.

Power Supply:

110/220/240 VAC

Electronics:

RFID Reader - 13.5 MHz ISO1563/18000-3, touch screen PC, printer, most data models supported.

Labels supported:

Ring, video, CD, DVD, book

Installation Requirements:

- One double switched socket outlet 450mm from floor level.
- One single IP addressed network point, same location as power point.
- SIP2 connection from ILS

AFI/EAS

AFI or EAS supported

Software included for issue and return, optional management, image and data capture applications

UL approved and FCC certified.